CHOPPER

LIGHTWEIGHT, WRAP-AROUND FIT

CHOPPER is the ideal model for optimum protection and comfort. With its ten-base frame CHOPPER will offer you the best protection for any situation.











SUPPLIED WITH

Adjustable cord CORDC



- **+** WRAP-AROUND FIT
- + ALL-ROUND VISION
- **+** COMFORTABLE, STRAIGHT TEMPLES



CHOPPER

LIGHTWEIGHT, WRAP-AROUND FIT

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
	Clear	CHOPSI	2C-1,2 😭 1 FT C€		Anti-scratch/anti-fog
CHOPPER	Smoke	CHOPSF	5-3,1 🖆 1 FT C€	≌ EN166 FT C€	Anti-scratch/anti-fog
	Yellow	CHOPSJ	2C-1,2 😭 1 FT €€	≌ EN166 FT C€	Anti-scratch/anti-fog

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

C€ European standard ☐ Manufacturer name

TECHNOLOGY

∠ESP

ESP, Extra Sensory Perception. An innovative coating to reduce dazzle and the harmful affects of blue light. B-ESP filters 57% of blue light, transmits 64% of visible light, 99.99% of UVA/UVB

PACKAGING AND EAN13 CODE						
	CHOPSI	CHOPSF	CHOPSJ			
Individual plastic bag	3660740005900	3660740005917	3660740005924			
10 safety spectacles per inner box	3660740105907	3660740105914	3660740105921			
300 safety spectacles per outer pack	3660740205904	3660740205911	3660740205928			

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- C€ European standard ☐ Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS				
LENSES	PC - 2,2 mm - Curve 10.5			
FRAME	PC			
TEMPLES	PC			
STRAP	Non applicable			
FOAM	Non applicable			
SPARE LENSES	No			













01/10/2013

Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessingtor Surrey - KT9 2NY Tél.: 00 44 (0)208 391 4700

Fax: 00 44 (0)208 391 4733 e-mail: sales@bolle-safety.co.uk

