

RUSH+

PANORAMIC AND SPORTY

The RUSH + adopts an ultra-sporty design with its co-injected and ultra-flexible temples ... and is 100% customisable.



Non-slip adjustable bridge



RUSHPFSPSI
(Rush+ clear with foam & strap)



26 g

Fully customise the RUSH +:
lens marking, temples colour ...

Informations & conditions : marketing@bolle-safety.com



RUSHPPSI



RUSHPPSF



RUSHPTWI



RUSHPPSIB




RUSHPPSIG



RUSHPPSIO



RUSHPPSIY



RUSHPPPSFY



RUSHPCSP



RUSHKITFS
Kit foam & strap



RUSHKITS
Strap only

- + UPPER PROTECTION**
- + PLATINUM® COATING (P)**
- + CO-INJECTED, ULTRA-FLEX TEMPLES**
- + NON-SLIP ADJUSTABLE BRIDGE**
- + BI-COLOUR TEMPLES DEPENDING ON VERSION**

bolle
SAFETY

RUSH+

PANORAMIC AND SPORTY

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
RUSH+	Clear	RUSHPPSI	2C-1,2 1 FT KN €	EN166 FT €	Anti-scratch/Anti-fog
	RUSH+ with foam & strap	RUSHPFSPSI	2C-1,2 1 FT KN €	EN166 FT €	Anti-scratch/Anti-fog
	Smoke	RUSHPPSF	5-3,1 1 FT KN €	EN166 FT €	Anti-scratch/Anti-fog
	Smoke	RUSHPPSFY	5-3,1 1 FT KN €	EN166 FT €	Anti-scratch/Anti-fog
	BCSP	RUSHPCSP	5-1,4 1 FT KN €	EN166 FT €	Anti-scratch/Anti-fog
	BTWILIGHT	RUSHPTWI	5-2 1 FT KN €	EN166 FT €	Anti-scratch/Anti-fog
	Clear	RUSHPPSIG	2C-1,2 1 FT KN €	EN166 FT €	Anti-scratch/Anti-fog
	Clear	RUSHPPSIB	2C-1,2 1 FT KN €	EN166 FT €	Anti-scratch/Anti-fog
	Clear	RUSHPPSIY	2C-1,2 1 FT KN €	EN166 FT €	Anti-scratch/Anti-fog
	Clear	RUSHPPSIO	2C-1,2 1 FT KN €	EN166 FT €	Anti-scratch/Anti-fog
	Kit foam & strap	RUSHKITFS	-	-	-
	Strap only	RUSHKITS	-	-	-

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s

Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles

N. Resistance to fogging

€ European standard Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s

Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

€ European standard Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

TECHNOLOGIES

BTWILIGHT

The new B-Twilight technology offers the advantages of ESP with a double anti-fog coating (on both sides of the lenses) to prevent fogging in the most challenging conditions.

Designed and used in low light conditions, it improves contrast. Its light transmission rate is perfect for outdoors, particularly early morning and late evening. B-Twilight filters 76% of blue light.

PLATINUM

The new exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

BCSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments.

CSP is also combined with the exclusive PLATINUM® coating that sustainably combats fogging.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.



21/12/2017

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY

RUSH+

PANORAMIC AND SPORTY

CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 9
FRAME	-
TEMPLES	PC + TPR
STRAP	Nylon/15mm/Adjustable
FOAM	SBR
SPARE LENSES	No

PACKAGING AND EAN13 CODE

	RUSHPPSI	RUSHPPSF	RUSHTWI	RUSHPFPSI	RUSHPPSIG	RUSHPPSIB	RUSHPPSIY	RUSHPPSIO
Individual plastic bag	3660740007041	3660740007058	3660740007065	3660740007577	3660740007157	3660740007171	3660740007140	3660740007164
10 safety spectacles per inner box	3660740107048	3660740107055	3660740107062	3660740107574	3660740107154	3660740107178	3660740107147	3660740107161
240 safety spectacles per outer pack	3660740207045	3660740207052	3660740207069	3660740207571	3660740207151	3660740207175	3660740207144	3660740207168

PACKAGING AND EAN13 CODE

	RUSHPPSFY	RUSHPCSP	RUSHKITFS	RUSHKITS
Individual plastic bag	3660740007935	3660740008444	3660740006488	3660740007546
20 foam and strap kits OR 40 foams only per inner box	3660740107932	3660740108441	3660740106485	3660740107543
240 foam and strap kits OR 480 foams only per outer pack	3660740207922	3660740208448	3660740206482	3660740207540



Non-contractual pictures

21/12/2017

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY