

SILEX

THE MODEL WITHOUT COMPROMISE

FLEX 160° technology that fits every face perfectly, flexible bi-material temples and absolute support without pressure points. SILEX has a panoramic vision, an ultra-wraparound protection, lenses with a refined design and coloured temples by Bollé Safety.

No compromise on performance, comfort, style and affordability, SILEX is suitable for all industries: construction, automotive, mining, production line.



SILEXPSI



SILEXPSF



SILEXPSJ + UNIVSTRAP



SILEXPSJ



UNIVSTRAP (optional)
Strap









30g

- + ULTRA-WRAPAROUND FRAME**
- + PC/TPR CO-INJECTED TEMPLES FOR GREATER COMFORT**
- + PANORAMIC FIELD OF VISION**
- + FLEX 160° TEMPLES**
- + OPTIONAL STRAP FOR REINFORCED SUPPORT**

bollé
SAFETY

SILEX

THE MODEL WITHOUT COMPROMISE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
SILEX	 Clear	SILEXPSI	 IO	AS/NZS 1337.1:2010	Anti-scratch/Anti-fog
	 Smoke	SILEXPSF	 I3	AS/NZS 1337.1:2010	Anti-scratch/Anti-fog
	 Yellow	SILEXPSJ	 IO	AS/NZS 1337.1:2010	Anti-scratch/Anti-fog
	Strap only (optional)	UNIVSTRAP	-	-	-

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' signifies that the product has been approved for the use both outdoors and indoors, and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses.

Ocular lens category:

- O. Range of luminous transmittance 80–100% (Clear & Yellow)
- 3. Range of luminous transmittance 8–18% (Smoke)

Others symbols:

 Manufacturer name

TECHNOLOGIES

FLEX 160°

Soft and ultra pliable, 160° FLEX frames can be used to adjust the space between the temples for better wearer comfort.

LENSES

- 2.2mm polycarbonate
- Anti-scratch/Anti-fog coating: Clear, Smoke , Yellow
- 99.9% UV 385 – Clear, Yellow
- 99.9% UV 400 – Smoke

FRAME MARKING

AS/NZS 1337.1:2010 Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm ball at 45 m/s.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND GTIN				
	SILEXPSI	SILEXPSF	SILEXPSJ	UNIVSTRAP
Individual plastic bag	9318330047161	9318330047178	9318330048472	9318330040865
10 safety spectacles per inner box	(01)19318330047168	(01)19318330047175	(01)19318330048479	-
240 safety spectacles per outer pack	(01)29318330047165	(01)29318330047172	(01)29318330048476	-

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	-
TEMPLES	PC + TPR
STRAP	Nylon/15mm/Adjustable
SPARE LENSES	No



Non-contractual pictures

17/03/2020

Bollé Safety AU Pty Limited
32–40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: sales@bollesafety.com.au

Hong Kong Bollé Safety
818, 8/F, Ocean Centre, Harbour City,
5 Canton Road, Tsim Sha Tsui,
Kowloon, Hong Kong
T.: +852 2732 5038

bollesafety.com.au

bolle
SAFETY