

EVOLite® Mid Peak OneTouch™ Slip Ratchet Non Vented

White / AJA160-000-100



DESCRIPTION

The EVOLite® is a breakthrough product enabling Health and Safety Officers to achieve new levels of compliance due to its unrivalled comfort. It is lightweight, extremely comfortable and fits the widest range of head shapes and sizes. The harness and shell are truly integrated as one to give the best performance by keeping it firmly rooted on the head, even when fully inverted. Gives added security and protection when working at height, in high winds, or when there is a high degree of activity, such as during motorway maintenance.

OPTIONS

White (AJA160-000-100) Blue (AJA160-000-500) Black (AJA160-001-100) Grey (AJA160-000-400)

Yellow (AJA160-000-200)

SAFETY STANDARDS

EN 397 • EN 50365



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



SPECIFICATIONS Peak Impact Resistance Mid 50 Joules EN 50365 ELECTRICAL INSULATION Lateral Deformation Yes 1000V Molten Metal Maximum Temperature Yes +50°C Minimum Temperature ABS Shell 2A.a. ABS -40°C Yes Textile Recyclable Yes Harness Depth Adjustment Slip Ratchet **3D Harness** Slip Universal Accessories Slot Ventilation Yes No Integrated Eyewear **Reflective Option** Optional Optional ID card holder **BSI Kitemark** Optional Yes Optional 2 point chinstrap (EN397 & EN 812 compliant) Optional 4 point chinstrap (EN397 Compliant) Optional Optional **JSPCheck** Product Weight Yes 328g

FEATURES



Supreme Comfort

A 6-point terylene cradle harness system & Egyptian cotton Chamlon[™] sweatband offers unrivalled comfort.



Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. Available with either the Revolution® wheel ratchet or the OneTouch[™] slip ratchet.



Accessories

A universal attachment slot enables firm fitting of a range of Surefit[™] safety visors, and ear defenders. EVOSpec[®] Integrated eyewear is also available.

LOGO



Back

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.





3D Adjustment

The textile harness features unique 1-2-3 point depth settings. This offers the most precise fit attainable on an industrial safety helmet.

CR2™ Reflective

Using Class RA2, high intensity reflective. CR2 is the biggest step-up in night time visibility / reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.

JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.

RANGE





VIDEOS

- www.youtube.com/watch?v=r9zutN49DO8
- www.youtube.com/watch?v=LdxMNctXLbg
- www.youtube.com/watch?v=4iv_k1SEs4g
- www.youtube.com/watch?v=WXD2v6an1as&t

DOWNLOADS

- Image Pack (ZIP)
- doc-invincible-evolite.pdf (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.