

TECHNICAL SPECIFICATION

RESPIRATORY PROTECTION



Flexinet® Mask FFP2 Valved (822)

Product Code: BER122-201-A00 / BER122-201-L1X



Description

The Flexinet™ disposable mask has an ergonomic 3D design to fit most face shapes, with extremely low breathing resistance and mesh outer shell to help the mask retain its shape.

- High efficiency (94% minimum) filtering

Options

Box of 10 code: BER122-201-A00

Retail pack x 1 code: BER122-201-L1X



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com
Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com.
Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.
Page 1 of 3 / Issued 04 Feb 21 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.




www.jsp-safety.com

sales@jsp-safety.com

UK tel: +44 (0)1993 826050

FEATURES



Comfort

A 360° comfort foam area around the inside of the mask provides a perfect fit



Protective Grill

Flexible cover to protect and retain the shape of the mask and protect the wearer against possible damage to the filter



Advanced Valve

Advanced design valve allows for lower breathing resistance

COMPATIBLE PRODUCTS

EVO® Gas Goggle
EVO® Goggle Double Lens
EVO® Goggle Single Lens
Sonis® Compact Ear Defenders
Sonis®1 Ear Defenders
Sonis®2 Ear Defenders
Sonis®3 Ear Defenders
Stealth™ 16G
Stealth™ 7000
Stealth™ 8000
Stealth™ 9000
Stealth™ Coverlite™ Overspec
Thermex™ Double Lens Goggle

ACCESSORIES

Portacount/AccuFIT Quantitative/Qualitative Face Fit Testing Kit & Spares

SAFETY STANDARDS

EN 149:2001 + A1:2009

CERTIFICATION

CE 682743 issued by BSI

SPECIFICATIONS

Classification

FFP2 (Filtering Facepiece Particulate - Valved)

Filter Type

P (Protects Against Solid and Liquid Aerosols)

Usage

NR (Non-Reusable)

(D) Resistance to dust clogging



Yes - D marking = passes optional clogging test

Activated Carbon Layer



No

Minimum Filtration Efficiency

94% For FFP2 Rated



Maximum Total Inward Leakage (TIL)

8%

Nominal Protection Factor (NPF)

12

UK Assigned Protection Factor (APF)

10

Mask Design

Mesh Outer Shell

Exhalation Valve



Advanced Valve

Toggle Adjustment Straps

Yes

Nose Bridge



Moulded

Latex Free

Yes

Mask Material

Polypropylene

Filter Shelf Life

5 Years



BSI Kitemark

Yes



Product Weight

22g (Approx)

APPLICATIONS

- Mining, Aggregates and Quarrying
- Agriculture
- Forestry & Landscaping
- Manufacturing
- Constuction & Infrastructure
- Scaffolding & Roofing
- Welding (mild)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com.

Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 04 Feb 21 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.



INSTRUCTIONS FOR USE

- Mask must be fitted in accordance with the instructions supplied
- Care must be taken to ensure that the correct mask type is selected for the work to be carried out
- If in doubt as to the type of mask required, seek professional guidance

CLEANING & MAINTENANCE

- Not Applicable - Disposable Product
- Store the masks out of sunlight away from chemicals in a dry atmosphere

LIMITATIONS OF USE

- Protection will only be offered if the mask is fitted correctly
- The mask, when in contact with the skin may cause allergic
- Do not use where exposure to chemical gases may be experienced
- Use in well ventilated areas only, which are not deficient in oxygen and do not contain explosive atmospheres
- Ensure good seal around the face is created before entering the hazard area
- The working life of the mask is nominally one day (this is based on a working day shift of 8 hours), however it may be affected by many factors, including work rate, airflow and concentration of any contaminant in the atmosphere. The mask should be changed immediately if,
 - a.) Breathing difficulties due to clogging are experienced,
 - b.) Breakthrough of a contaminant is detected by smell, taste or any other means, or
 - c.) The mask becomes damaged



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com
Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com.
Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.
Page 3 of 3 / Issued 04 Feb 21/ Copyright 2018 – 2020, JSP Limited. All Rights Reserved.

