




**GREEN
DEVIL**

**Breathing
Protection**

27.06.2022

Product data sheet greendevil AF-2V FFP2 NR D



Product information

Product features	<ul style="list-style-type: none"> • Particle-filtering folding mask with exhalation valve • Protection level FFP2 • Innovative design with optimized shape • Soft material edges for more high wearing comfort • Continuous head band (adjustable) for a comfortable and secure fit • Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask • Flexible and adjustable nose clip • Compatible with safety eyewear • Soft sealing lip (nose area) guarantees a secure, comfortable sealed position of the mask • Mask fulfils the requirements of the dolomite dust test (D) 										
Materials	<table border="0"> <tr> <td>Headband:</td> <td>Textile</td> </tr> <tr> <td>Nose clip:</td> <td>Metal</td> </tr> <tr> <td>Filter / mask:</td> <td>Melt Blown PP, Polyester</td> </tr> <tr> <td>Sealing lip:</td> <td>PVC foam</td> </tr> <tr> <td>Valve:</td> <td>PP</td> </tr> </table>	Headband:	Textile	Nose clip:	Metal	Filter / mask:	Melt Blown PP, Polyester	Sealing lip:	PVC foam	Valve:	PP
Headband:	Textile										
Nose clip:	Metal										
Filter / mask:	Melt Blown PP, Polyester										
Sealing lip:	PVC foam										
Valve:	PP										
Weight	18.7g										
Standard	EN 149:2001 + A1:2009										

Versions

Article number	Colour/Version	Retail unit
AF-2V	folding mask FFP2, white with valve	15 pcs. per box

Packaging sizes

Box: 15 pcs	approx. 22 x 8.5 x 25.5 cm
Outer Carton: 300pcs	approx. 43.5 x 45 x 52 cm

Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance 30l/min.	Inhalation resistance 95l/min.	Exhalation resistance 160l/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
FFP3	1,0	3,0	3,0

Areas of use*

The respiratory protection mask can be used against solid, aqueous and nonvolatile liquid aerosols up to 30 times the respective limit values.	Woodworking, hard wood, chromium, asbestos (short periods of work), stainless steel, lead, welding, dust that contain beryllium, arsenic, cadmium or cobalt. Medical waste disposal, fungal spores, legionella bacteria, infections, viruses, bacteria, enzyme, nanoparticles.
---	--

*Please note that the above-mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Geendevil accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advise.

MJS Safety, Unit 55 D/E Maple Avenue, Stillorgan Industrial Park, Stillorgan, Co. Dublin. Ireland.