

Product data sheet greendevil AF-3V FFP3 NR D



**Product information**

<p><b>Product features</b></p>	<ul style="list-style-type: none"> <li>• Particle-filtering folding mask with exhalation valve</li> <li>• Protection level FFP3</li> <li>• Innovative design with optimized shape</li> <li>• Soft material edges for more high wearing comfort</li> <li>• Continuous head band (adjustable) for a comfortable and secure fit</li> <li>• Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask</li> <li>• Flexible and adjustable nose clip</li> <li>• Compatible with safety eyewear</li> <li>• Soft sealing lip (nose and chin area) guarantees a secure, comfortable sealed position of the mask</li> <li>• Mask fulfils the requirements of the dolomite dust test (D)</li> </ul>
<p><b>Materials</b></p>	<p>Headband: Textile          Nose clip: Metal          Headband clips: Polypropylene          Filter / mask: Melt Blown PP, Polyester          Sealing lip: PVC foam          Valve: PP</p>
<p><b>Weight</b></p>	<p>18.7g</p>
<p><b>Standard</b></p>	<p>EN 149:2001 + A1:2009</p>

## Versions

Article number	Colour/Version	Retail unit
AF-3V	folding mask FFP3, white with valve	15 pcs. per box

## Packaging sizes

Box: 15 pcs	approx. 22 x 8.5 x 25.5 cm
Outer Carton: 300pcs	approx. 43.5 x 45 x 52 cm

## Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance 30l/min.	Inhalation resistance 95l/min.	Exhalation resistance 160l/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
FFP3	1,0	3,0	3,0

## Areas of use\*

The respiratory protection mask can be used against solid, aqueous and nonvolatile liquid aerosols up to <b>30 times</b> the respective limit values.	Woodworking, hard wood, chromium, asbestos (short periods of work), stainless steel, lead, welding, dust that contain beryllium, arsenic, cadmium or cobalt. Medical waste disposal, fungal spores, legionella bacteria, infections, viruses, bacteria, enzyme, nanoparticles.
---	--

\*Please note that the above-mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Greendevil accepts no liability for any possible harm or damage which may result from this information.  
This data sheet does not replace a detailed risk assessment nor seeking specialist advise.

MJ Scannell Safety, Unit 55 D/E Maple Avenue, Stillorgan Industrial Park, Stillorgan, Co. Dublin. Ireland.