



PRODUCT NUMBER: 1032333
Miller kernmantel restraint lanyard 1 meter with 2 CS20 karabiners

Miller kernmantel restraint lanyard 1 meter with 2 steel screw gate karabiners.



Overview

Reference Number

1032333

Product Type

Fall Protection

Range

Restraint Lanyards

Brand

Miller by Honeywell

Industry

- Building and Construction
- Utilities

Product Use

Restraint lanyards are used to restrict the worker's movement to prevent him reaching a location where a fall hazard exists.

Features & Benefits

Feature

New Design : * The new Kernmantel rope is manufactured with light green rope with black stripes , which are highly visible from a distance increasing the safety at work. * The stitches are highly visible which facilitates the safety check before use.

Benefit

The kernmantel lanyard is 2 times more resistant to the abrasion than a standard rope.

Technical Description

Length

1 M.

Weight

0,420 KG.

Breaking Strength

> 22 KN

Operating Temperature

-30°C to +50°C

Rope**Rope Raw Material**

Kernmantel Ø 11 mm. Polyester sheath and polyamide core

Connector**Connector Type**

Screw gate karabiners

Connector Raw Material

steel

Connector Opening

17 mm

Connector Breaking Strength

> 25 KN

Connector Standard

EN 362 : 2004

Certifications**EU Category PPE**

3

Quality Assurance

ISO 9001 / 2000

EU Certification

EU Attestation

Certifications

- EN 354
- EN 358 : 1999

REACH**EU Regulation 1907/2006 (REACH) Compliance**

The substance(s) listed below may be contained in this product above the threshold level of 0.1% by weight of the listed article.

Product Reference Sold in Europe	Substance > 0.1%
Substance Name	CAS Number
No Substance Content	

Additional Information**User Manual**

NT90004208 IND L

User Information Sheet

User manual

Maintenance

Life Cycle

Life expectancy of our harnesses is 10 years from the date of manufacture.

Care Instructions

Some factors can contribute to reduce the performance or life expectancy of the product:

- Incorrect stocking
- Incorrect use
- Stopping a fall
- Mechanical deformation or cut
- Contact with chemical products (an acid or a base)
- Exposure to extreme heat sources > 60°C
- Exposure to UV rays

Please remember that:

- the product must be checked at least once a year by a qualified person. This inspection must be registered.
- before each use, the product must be visually inspected by the user.

The compulsory annual inspection will be the deciding factor as to whether your PPE should be put back into service or not.