









CERLAK

Description	Kit designed to be used on arm elevating working platforms, for scaffoldings and various applications in the construction industry. The kit includes a harness , one single lanyard with energy absorber equipped with connectors.
Type of protection	Fall arrest system
Type of work	 Construction industry
	 Arm elevating working platforms
	 Scaffoldings








Packaging	Code	Size	Quantity
	A090-1105.I2	M-2XL (one size)	1 pc

CERBERO

Description	A basic harness, easy to fit and adjust.		
Standard	EN 361:2002		
Attachment Points		Device with two attachment points for fall arrest, one on the rear and one on the front (obtained by connecting two semi-attachment points A/2). The large, functional dorsal hook is made of forged steel.	
Adjustment	SINGLE - on the lower part of the harness		
Metal components	Zinc-plated steel		
Straps	45 mm and 30 mm wide polyester		
Plus	<p>EXTREME LOAD 150 kg</p> 	The additional test certifies the resistance of Cofra devices against a maximum nominal load of 150 kg, compared with the 100 kg of the normal devices on the market.	
	<p>HIGH-TENACITY POLYESTER STRAP</p> 	The strap is made of high-tenacity polyester making it highly resistant to tear and abrasion.	
	<p>STEEL COMPONENTS</p> 	Steel resists perfectly to the considerable stresses which develop during a fall. All steel components have undergone anticorrosive galvanisation treatment with zinc or chrome.	
Size / Weight (pc.)	M-2XL (one size) / 820 g		

SIZE CHART

<p>SIZE</p> 	HARNESS			
	A (cm)	B (cm)	C (cm)	H (cm)
M-2XL	96/116	84/104	56/70	172/190

DULFER		
Description	Single lanyard with integrated energy absorber. Equipped with a base steel connector and anchorage steel connector. Static lanyard with a diameter of 11 mm.	
		
Locking system	<p>SCREW</p> 	The Screw lock is the simplest locking mechanism while maintaining a high level of safety.
Plus	<p>KERNMANTLE ROPE</p> 	The static rope with kernmantle weave is characterised by a composite structure comprising a stress-resistant inner kern and an outer mantle to protect the kern from abrasion, UV rays, weather conditions, oil, fire and heat. In addition, the mantle acts as a visible indicator of the rope's wear.
	<p>STEEL COMPONENTS</p> 	Steel resists perfectly to the considerable stresses which develop during a fall. All steel components have undergone anticorrosive galvanisation treatment with zinc or chrome.
Length	2 m	
Standard	EN 355:2002	
Maximum opening of the absorber	1,4 m	
Weight (pc.)	1030 g	
ROPE		
Diameter	11 mm	
Type	Static rope with kernmantle weave	
Material	Inner kern: Nylon	
	Outer mantle: Nylon	
CONNECTORS		
	Connector at the end of the absorber	Free end connector
Description	Base connector	Anchorage connector
Standard	EN362-B	EN362-A
Material	Zinc-plated steel	Zinc-plated steel
Opening	18 mm	54 mm
Locking system	SCREW - Screw lock	Back safety lever
Minimum resistance for the major axis with closed and locked lever	25 kN	25 kN

WRAPPER BAG		
Description	Polyester sack, designed to place the fall protection devices inside.	
		
Material	Sack	Polyester
	Pocket	PVC

STOCKING CONDITIONS AND MAINTENANCE	
Lifetime	The lifetime of the unused metal products is unlimited. The lifetime of the unused not metal products is 10 years under normal conditions. Once the product is used, its lifetime cannot be estimated since there are factors which could considerably reduce its lifetime such as: intense use; damage to product components; contact with chemical substances; high temperatures, abrasions, cuts, violent impacts, wrong use and stockage.
Cleaning	<p>Cleaning the textile and plastic parts: wash only with cold fresh water and neutral soap and allow to air dry, away from direct sources of heat.</p> <p>Cleaning the metallic parts: wash with cold fresh water and dry.</p> <p>Lubrication : lubricate the lever mechanism with silicone based lubricants.</p> <p>If the equipment becomes wet either during use or after cleaning, it must be left to air dry and kept away from direct heat.</p>
Transport and stocking	Keep the device in its original packaging. During transport and storage, keep this product away from light and sources of heat, from high humidity, from sharp edges or objects, from corrosive substances and from any other possible cause of damage or deterioration, in order to preserve the performance and safety of the product. Keep this product in a cool, dry place to preserve the performance and safety of the product.