



Prod. Ref.	80220-000
Safety cat.	S3 WR HRO SRC
Range of sizes	39 - 48 (6 - 13)
Weight (sz. 8)	793 g
Shape	B
Width	11

Description: Brown/black water repellent Pull-Up nubuck ankle boot, **GORE-TEX® Performance Comfort Footwear** membrane lining, antistatic, anti-shock, slipping resistant, non metallic **APT Plate** midsole **Zero Perforation**

Plus: Full **SOFT-BED** footbed, made of soft and scented polyurethane, antistatic, anatomic, holed, soft and comfortable. The upper layer absorb moisture and keep the foot dry. Cold and heat insulation. Arch support made of polycarbonate and fibreglass conveniently placed between heel and sole, which provides support and protection of the plantar arch, thus preventing harmful bendings. Outsole resistant to +300°C (1 minute contact). **Leather toe cap protection**

Suggested uses: Construction, maintenance, industries. Footwear for wet environments

Care and maintenance: Clean after each use and dry off away from direct heat. Avoid contact with aggressive chemicals or extreme temperature. Avoid immersion in sea water, lime water or cement mixed with water

MATERIALS / ACCESSORIES

SAFETY TECHNICAL SPECIFICATIONS

		Clause EN ISO 20345:2011	Description	Unit	Cofra result	requirement
Whole footwear	Water resistance	5.15.1	Water resistance (area of water penetration after 1000 paces in a surface flooded with water)	cm ²	≤ 3	≤ 3
Complete shoe	Toe cap: non metallic TOP RETURN toe cap, impact resistant until 200 J and compression resistant until 1500 kg	5.3.2.3	Shock resistance (clearance after shock)	mm	15	≥ 14
	Anti perforation midsole: in multi-layers highly tensile fabric, penetration resistant, Zero Perforation	5.3.2.4	Compression resistance (clearance after compression)	mm	14,5	≥ 14
	Antistatic shoe: the bottom is fit for the dissipation of electrostatic charges	6.2.1	Penetration resistance	N	To 1100 N No Perforation	≥ 1100
	Energy absorption system	6.2.2.2	Electric resistance			
			- wet	MΩ	45	≥ 0.1
			- dry	MΩ	880	≤ 1000
Upper	Brown water repellent Pull-Up nubuck thickness 1,6/1,8 mm	6.2.4	Shock absorption	J	32	≥ 20
		5.4.6	Water vapour permeability	mg/cmq h	> 4,2	≥ 0,8
			Permeability coefficient	mg/cmq	> 42,9	> 15
		6.3.1	Water absorption		28%	≤ 30%
			Water penetration		0,0 g	≤ 0,2 g
Lining	GORE-TEX® membrane, breathable and abrasion resistant, colour grey thickness 1.2 mm	5.5.3	Water vapour permeability	mg/cmq h	> 4,7	≥ 2
			Permeability coefficient	mg/cmq	> 38,2	≥ 20
Sole	Polyurethane/Nitrile rubber , antistatic, resistant to high temperatures, directly injected in the upper:	5.8.3	Abrasion resistance (lost volume)	mm ³	105	≤ 150
	Outsole: black nitrile rubber, slipping resistant, abrasion resistant, hydrocarbons resistant and heat resistant.	5.8.4	Flexing resistance (cut increase)	mm	1,5	≤ 4
	Midsole: black polyurethane, low density, comfortable and anti-shock.	5.8.6	Interlayer bond strength	N/m	4	≥ 3
	Adherence coefficient of the sole	6.4.4	Hot resistance (300 °C)	----	any melting	any melting
		6.4.2	Hydrocarbons resistance (ΔV = volume increase)	%	1,6	≤ 12
		5.3.5	SRA : ceramic + detergent solution – flat		0,54	≥ 0,32
			SRA : ceramic + detergent solution – heel (contact angle 7°)		0,50	≥ 0,28
			SRB : steel + glycerol – flat		0,23	≥ 0,18
			SRB : steel + glycerol – heel (contact angle 7°)		0,18	≥ 0,13