



# SPECIFICATION SHEET

## GLOVEZILLA TITAN ARMOUR NEEDLESTICK GLOVE



Product Code:

GZ67

Selling UOM:

Pair

Pack Size:

1

### FEATURES

- Dependable grip, excellent flexibility and a comfortable ergonomic shape.
- Puncture-resistant with latex coating
- Lined with two layers of Titan Armour
- Makes a great general-purpose work glove
- ASTM F2878 14.4 newtons of puncture protection (hypodermic needle)

- EN388: 2016
- Level 2 - Abrasion
- Level X - Cut Resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 4 - Puncture
- Level F - ISO 13997 Cut Resistance

- EN 407: 2004
- Level X - Burning Behaviour
- Level 2 - Contact Heat
- Level X - Convective heat
- Level X - Radiant heat
- Level X - Small splashes of Molten Metal
- Level X - Large splashes of Molten Metal

• Please note: there is no European standard for needle resistance. Current industry practice is to utilize the American Standard ASTM F2878 as a guide, and to allow comparisons between different products. These products are not needle proof. Your own risk assessment therefore needs to be undertaken to decide the suitability of this product.



Packaging Waste	Type	Units	Weight(g)	Length(mm)	Width(mm)	Height(mm)
Cardboard	Inner	40	9.79			
Paper	Inner	40	4.86			
Plastic	Inner	40	4.62			
Plastic	Inner	8	13.35			
Cardboard	Outer	1	740.00	698.00	304.00	212.00
<b>Carton Weight:</b>		0.00kg				