



TEGERA® 7390



[Learn more](#)

Chemical protection glove, winter-lined, 0,4* mm (*chem-layer) PVC (Vinyl), fully dipped, sandy finish, acrylic, fleece, Cat. III, for heavy work

CHARACTERISTICS

- Good fit
- Flexible
- Very durable
- Warm
- Good grip
- Comfortable

FUNCTIONS

- Waterproof
- Protection against chemicals



PREVENTS RISK OF

corrosive injuries, contact with dirt, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

chemical risk environments, environments hazardous to health, corrosive environments, outdoors, moist environments, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

building and construction, hvac installation, construction, soil preparation, concrete work, airport work, mining, agricultural work

PRIMARY INDUSTRIES OF USE

agriculture, mining, oil, gas, petrochemical, chemical

TYPE OF WORK

Heavy weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE Chemical protection gloves, Cold insulation gloves

CATEGORY Cat. III

THICKNESS 0,4* mm (*chem-layer)

LINING Winter-lined

LINING MATERIAL Fleece, Acrylic

LENGTH 300 mm

GRIP DESIGN Sandy finish

ANTIBACTERIAL/BIOCIDAL TREATMENT Pyrithione zinc (CAS number 13463-41-7)

COLOUR Blue

PAIRS PER: BUNDLE/CARTON 6/36

AQL 0.65

DISPLAY TYPE Bulk pack

DIPPING Fully dipped

DIPPING MATERIAL PVC (Vinyl)

CUT RESISTANCE (EN ISO 13977) TDM: N



EN 511:2006
121

EN ISO 21420:2020



EN 388:2016+A1:2018
4131X



Information/UIS



EN ISO 374-5:2016



EN ISO 374-1:2016/A1:2018 Type A
AKLNMNOPT

EN 511 cl. 5.2 Flexibility
behavior (-20°C)

EN 511 cl. 5.4 Extreme cold
flexibility (-50°C)

TEST ACCORDING TO EN ISO 374-1:2016

Tested chemical	A	K	L	M	N	O	P	T
Permeation level	3	6	4	5	2	2	6	6
Degradation %	-9,1	-7,3	2,7	50,1	9,8	20,3	3,2	-4,0

SIZE	ARTICLE NUMBER	EAN
9	7390-9	7392626075221
10	7390-10	7392626008311



Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com