



## TEGERA® 9128



Learn more

Ergonomic, waterproof glove featuring Microthan+® touchscreen capabilities. Thinsulate™ technology and inner fleece helps trap body heat. Durable Microthan®+ synthetic leather. Good grip on slippery surfaces thanks to diamond grip pattern. High visibility yellow on back offers extra safety in low light conditions. 360° elasticated cuff for better fit EN 388:2016, 1121X EN 511:2006, 111

### CHARACTERISTICS

- Perfect fit
- Flexible
- Durable
- Excellent grip
- Extra comfortable

### FUNCTIONS

- Waterproof
- Reinforced index finger
- Reinforced seams
- Reflector
- For touchscreen
- Chrome free
- Pre-curved fingers
- Specially designed thumb
- Reinforced fingertips
- High visibility colour
- Knuckle protection
- Windproof
- Ergonomically shaped
- Specially designed details

MicroThan®+

AQUATHAN®



Thinsulate™  
INSULATION

**PREVENTS RISK OF**

chrome allergy, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with moisture, contact with damp, contact with cold

**PRIMARY ENVIRONMENTS OF USE**

dark environments, cold environments, wet environments, moist environments, dirty environments, harsh environments

**PRIMARY AREAS OF USE**

agricultural work, airport work, building and construction, construction, engineering, forest work, machine driving, machine operating, transport work, warehouse work, wood industry work

**PRIMARY INDUSTRIES OF USE**

agriculture, mining, pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, building and construction, logistics, facilities, service, retail

**TYPE OF WORK**

Medium weight

**SPECIFICATION**

**TYPE** All-round work gloves, Cold insulation gloves

**CATEGORY** Cat. II

**COLLECTION** PRO

**PALM MATERIAL** Microthan®+

**BACK MATERIAL** Polyester

**LINING** Winter-lined

**LINING MATERIAL** Thinsulate™ 40g, Fleece

**LENGTH** 240-275 mm

**GRIP DESIGN** Diamond grip pattern

**COLOUR** Yellow, Black

**PAIRS PER: BUNDLE/CARTON** 6/60

**DISPLAY TYPE** Hook with hangtag

**FASTENING** Elasticated 360°

**CLO INSULATION RATING** 0,7 m<sup>2</sup>·K/W

**CUT RESISTANCE (EN ISO 13977) TDM:** N

**INNER MATERIAL SPECIFICATION** Polyester

**MIDDLE MATERIAL SPECIFICATION** Polyethylene

**OUTER MATERIAL SPECIFICATION** Polyurethane, Nylon, Polyester



EN 420:2003  
+A1:2009



Short model (EN 420)



EN 388:2016  
1121X



Information/UIS



EN 511:2006  
III

SIZE	ARTICLE NUMBER	EAN
6	9128-6	7340118354798
7	9128-7	7392626070868
8	9128-8	7392626070882
9	9128-9	7392626070905
10	9128-10	7392626070820
11	9128-11	7392626070844
12	9128-12	7340118354781

# ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | [info@ejendals.com](mailto:info@ejendals.com) | [order@ejendals.com](mailto:order@ejendals.com)